

Attorney Docket No.: A4938.01/T37310

AMAT No.: 004938.01/FET/DV

TTC No.: 016301-037310US

PATENT APPLICATION

FAULT DETECTION AND VIRTUAL SENSOR METHODS FOR TOOL FAULT MONITORING

Inventor(s):

Terry Reiss
a citizen of the United States of America
397 Bay Street
San Jose, CA 95123

Dimitris P. Lymberopoulos
A Citizen of Greece,
6160 Paseo Pueblo Drive
San Jose, California 95120

Assignee:

APPLIED MATERIALS, INC.
P.O. Box 450A
Santa Clara, CA 95052
A Delaware corporation

Entity: Large

TOWNSEND AND TOWNSEND AND CREW LLP
(650) 326-2400

FAULT DETECTION AND VIRTUAL SENSOR METHODS FOR TOOL FAULT MONITORING

CROSS-REFERENCE TO RELATED APPLICATION

5 The present nonprovisional application claims priority from United States Provisional Patent Application 60/232,598 (Attorney Docket No. AM4938/T37300), filed September 14, 2000, which is hereby incorporated by reference.

BACKGROUND OF THE INVENTION

10 Semiconductor processing tools are highly complex devices. Their performance in real time is typically evaluated by monitoring values of a large number of tool sensors that reflect operational parameters such as temperature, pressure, and power. This tool evaluation may be conducted by comparing empirically measured
15 sensor values to values predicted by a model.

 An example of a model for predicting the behavior of a semiconductor processing tool is the Universal Process Modeling (UPM) technique. This model was developed by Triant Technologies, Inc., of Nanaimo, British Columbia.

 Fig. 11 is a simplified schematic diagram illustrating the UPM
20 technique. As shown in step A of Fig. 11, semiconductor processing tool 1101 is operated, and input vector 1102 comprising values 1104 for tool sensors 1106 is sampled at a time during the tool run (step A). Sampled input vector 1102 is then compared with reference data library 1112 (step B). Reference data library 1112 represents a compilation of vectors 1150-1157 from previous normal operation of
25 semiconductor processing tool 1101. Vectors 1150-1157 of reference library 1112 include a value for each sensor of input vector 1102.

 As a result of the comparison of step B, vector subset 1110 comprising vectors 1150, 1153, 1156, and 1157 is compiled from reference data library 1112 utilizing a nearest neighbor selection process between input vector 1102 and the vectors
30 of reference data library 1112 (step C). Vectors 1150, 1153, 1156, and 1157 of vector subset 1110 reflect sensor values of previous normal operation of tool 1101 that most closely resemble input vector 1102. A variety of techniques may be employed in the

nearest neighbor selection process as known to those of skill in the art. Precise details of the nearest neighbor selection process utilized by the UPM model are proprietary.

Next, vectors 1150, 1153, 1156, and 1157 of subset 1110 are combined to produce a single output prediction vector 1116 (step D). Output prediction vector 1116 reflects the state of semiconductor processing tool 1101 in relation to previous normal operation. Output prediction vector 1116 may be communicated to the tool operator in several ways. For example, as shown in Fig. 11, values 1118 of individual sensors 1120 of output prediction vector 1116 may be combined to produce a single fault detection index 1114 that reflects the values of all of the tool sensors (step E). Alternatively, as shown in Fig. 12, values 1118 representing each individual sensor 1120 of the output prediction vector may be plotted along spokes 1202 of "bull's eye" graph 1200, with radial distance 1204 representing deviation of the measured sensor value from expected values.

One aspect of the UPM modeling technique just described is that it does not consider possible correlation between groups of related sensor values, such as related tool pressures, related tool temperatures, or related tool powers. Rather, all sensors are accorded equal weight in generating the fault detection index. This approach thus does not include potentially valuable correlation between related operational parameters that could provide more reliable fault detection information.

Moreover, while the bull's eye graph of Fig. 12 provides the tool operator with an organized presentation of real-time tool operational parameters, the operator must still continuously monitor each of the tool sensors in order to detect a fault. Doing this for a large number of sensors may occupy the operator's attention, diverting him or her from other important tool management tasks.

Another aspect of the modeling technique shown in Fig. 11 is that selection of nearest neighbor vectors to form the vector subset and the output prediction vector is based solely upon the sensor values. Other potentially relevant information, for example the time during the tool run at which the input vector is sampled, is not taken into account in the nearest neighbor selection process. This may affect the model's accuracy where the input vector and the library vector are similar merely by chance, for example where a temperature component of the input vector is measured at an early stage (ramp up) of a tool run, while the temperature component of the library vector is measured at a late stage (ramp down) of a tool run. In such a case values of

the temperature component of the input and library vectors may be similar by chance, but the library vector is not otherwise an accurate prediction of the input vector.

Accordingly, more sophisticated techniques for fault detection of semiconductor processing tools are desirable.

5

SUMMARY OF THE INVENTION

Embodiments of the present invention relate to methods for fault detection of a semiconductor processing tool. In particular, embodiments of the present invention relate to methods and apparatuses that employ tool modeling techniques that enhance the accuracy of fault detection.

One embodiment of a fault detection method in accordance with the present invention comprises sensing a group of correlating operational parameters of a semiconductor processing tool operating under a recipe, and sensing non-correlating operational parameters of the tool operating under the recipe. An input vector is formed including the group of correlating operational parameters and the non-correlating operational parameters. The input vector is compared to a reference data library comprising vectors from previous tool runs utilizing the recipe. Nearest neighbor vectors to the input vector are selected from the reference data library based upon a similarity with only the group of correlating operational parameters. A vector subset is compiled from the selected nearest neighbor vectors. The vector subset is combined into an output prediction vector, and a fault detection index is generated from the output prediction vector.

This and other embodiments of the present invention, as well as its advantages and features, are described in more detail in conjunction with the text below and attached figures.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1A is a simplified flow chart summarizing one embodiment of the method according to the present invention.

Fig. 1B is a schematic diagram illustrating operational details of the method shown in Fig. 1A.

Fig. 2A plots values for foreline pressure for an initial series of test runs of a plasma etching tool.

Fig. 2B plots values for foreline pressure for an intermediate series of test runs.

Fig. 2C plots values for foreline pressure for a later series of test runs.

Fig. 3 plots the second fault detection index of TABLE 2 over a series of
5 test runs.

Fig. 4 plots the third fault detection index of TABLE 2 over the same series of test runs of Figure 3.

Fig. 5 plots the fourth fault detection index of TABLE 2 over the same series of test runs of Figure 3.

Fig. 6 plots the first fault detection index of TABLE 2 over the same series of test runs of Figure 3.

Figs. 7A plots gas 1 inlet pressure for portion Z of the test runs of
Figures 3-6

Figs. 7B plots foreline pressure for portion Z of the test runs of Figures
15 3-6.

Figs. 7C plots throttle valve for portion Z of the test runs of Figures 3-6.

Figs. 7D plots chamber pressure for portion Z of the test runs of Figures
3-6.

Fig. 8A plots fault detection index versus time for a fault detection
20 method which does not utilize cluster sensor information in the selection process of the nearest neighbor vectors.

Fig. 8B plots fault detection index versus time for a fault detection method which utilizes cluster sensor information in the selection process of the nearest neighbor vectors.

Fig. 9A plots actual and predicted susceptor temperature over time for a properly functioning etch tool.

Fig. 9B plots actual and predicted susceptor temperature over time for a method in which susceptor temperature is an active sensor type.

Fig. 9C plots actual and predicted susceptor temperature over time for a
30 method in which susceptor temperature is a passive/inclusive sensor type.

Fig. 10 shows a simplified view of an apparatus configured to practice an embodiment of a method in accordance with the present invention.

Fig. 11 is a simplified schematic diagram illustrating the steps of the UPM technique.

Fig. 12 is a “bull’s eye” graph of a conventional fault detection method.

DESCRIPTION OF THE SPECIFIC EMBODIMENTS

As mentioned above, embodiments of the invention relate to methods and apparatuses that employ tool modeling techniques that enhance the accuracy of fault detection in semiconductor processing tools. In order to better appreciate and understand the present invention, reference is made to Figs. 1A and 1B and the accompanying text below. Fig. 1A is a simplified flow chart showing the steps according to one embodiment of the method according to the present invention, while Fig. 1B is a schematic diagram illustrating operational details of one example of the method shown in Fig. 1A used in conjunction with detecting faults during the operation of a plasma etching tool 102. Reference to plasma etching tool 102 is made for exemplary purposes only. It is to be understood that the present invention is applicable to detecting faults in other semiconductor fabrication tools including CMP tools, deposition tools and ion implant tools among others.

Before utilizing the present invention to detect tool faults, a fault detection model must be developed. Developing the fault detection model includes associating various characteristics of tool 102 with sensors that are included in vectors of the model (Fig. 1A, step 2). As used herein, the term “sensor” refers to an operational parameter of the semiconductor fabrication tool. Sensors can be of different types, as is described in more detail below. As used herein, the term “sensor types” refers to the role played by a particular sensor value in modeling and fault detection processes. A particular sensor type may or may not represent a tool operational parameter that is measured in real time.

In the example shown in Fig. 1B, there are seven different sensors: chamber pressure sensor 106a, throttle valve pressure sensor 106b, foreline pressure sensor 106c, gas 1 pressure sensor 106d, out 1 sensor 122, cluster sensor 118 and susceptor temperature sensor 120. It is to be understood that the seven sensors illustrated in the example are for exemplary purposes only. A typical fault detection model according to the invention as employed in a production environment will include considerably more than seven sensors.

After the various sensor are defined and assigned sensor types, data is collected during acceptable runs of the tool under a specific recipe and associated with the defined sensors (Fig. 1A, step 4). Next, a model representing operation of the tool

is constructed from the collected data (Fig. 1A, step 6). The model includes a reference data library, as well as rules for producing an output vector and fault detection index from data of an input vector that is compared to the reference library.

An example of a reference data library is shown in Fig. 1B as library 112. Reference data library 112 includes a plurality of reference data vectors 170-179 compiled from the collected data. Each vector includes as components the sensors defined by the model, as well as the collected data that is associated with each sensor. Thus, each vector in library 112 of Fig. 1B includes seven sensors. The data in library 112 represents parameters of tool 102 during proper operation under a specific plasma etching recipe. Rules for producing the output vector and fault detection index from the model further include, among others, rules assigning weights to certain sensors and rules to decide comparison thresholds.

Once library 112 is compiled and the fault detection model is completed, the model is ready to monitor tool 102 for faults in a production environment where tool 102 is operated under the specific recipe used to produce reference data library 112. During such use, an input vector 104 is sampled from the tool (Fig. 1A, step 8). Vector 104 includes the same sensors as the vectors in library 112. Once generated, vector 104 is input to the fault detection model in order to generate a fault detection index.

As shown in Fig. 1A, the fault detection index is created using a multistep process where first input vector 104 is compared to library 112 using a nearest neighbor approach to detect similar reference vectors (Fig. 1A, step 10). Next, the library vectors most similar to input vector 104 are compiled into a vector subset 108 (Fig. 1A, step 12). An output prediction vector 116 is then generated from the vector subset (Fig. 1A, step 14) and finally, a fault detection index 114 is generated from prediction vector 116 (Fig. 1A, step 16). Specific details concerning generation of fault detection index 114 during steps 10-16 according to one embodiment of the invention are discussed below with respect to Fig. 1B. The generation of the fault detection index is based, in part, on applying different rules to different types of sensors. Thus, in order to better understand this example, a description of the different sensor types is in order.

As previously mentioned, there are four different sensor types: active sensors, cluster sensors, passive/inclusive sensors and synthetic sensors. Active sensors are sensors that represent a group of correlating operational parameters. Embodiments

of the invention group correlating active sensors together as one technique to improve fault detection. Sensor grouping enables a specialized fault detection index 116 to be calculated based upon tool operational parameters known to correlate with one another. Examples of correlating sets of tool operational parameters may include sets of tool
5 temperatures or sets of tool pressures. Sensor grouping eliminates coincidences in tool data that could represent a fault, when in fact no tool fault has occurred.

In the example of Fig. 1B, it is known from operator experience that one group of correlating parameters of plasma etching tool 102 relates to pressure.

Accordingly, chamber pressure sensor 106a, throttle valve pressure sensor 106b,
10 foreline pressure sensor 106c and gas 1 pressure sensor 106d are all classified as active sensors. As explained in detail below, active type sensors are utilized in the selection process of the nearest neighbor vectors to compile a related vector subset, and they are also included in generating the fault detection index from the output prediction vector.

Another technique used by embodiments of the invention includes
15 refining the nearest neighbor selection process by including criteria other than similarity in the value of vector components. For example, Fig. 9A plots predicted and measured values for susceptor temperature of a plasma etching tool that is functioning normally. Susceptor temperature is cyclical over time, with an increase in susceptor temperature during first stage 900 of the etch process followed by a decline in susceptor
20 temperature during second stage 902 of the etch process.

Embodiments of the invention reference the stage of the plasma etching process when the input vector is measured in the selection of nearest neighbor vectors. For example, as shown in Fig. 9A susceptor temperature 904 of an input vector measured during first stage 900 of the etch process may be the same as susceptor
25 temperature 906 of a library vector measured during second stage 902 of the etch process. In such a case, while susceptor temperatures 904 and 906 may happen to be the same, the library vector is otherwise not an accurate prediction of the input vector. Accordingly, embodiments of the invention employ a cluster type sensor, such as
30 sensor 118, to represent the stage in the plasma etching process of tool 102 at which input vector 104 is sampled. As described in detail below, cluster type sensor values are included in the nearest neighbor selection process, but are not included in calculating the fault detection index.

A third type of sensor, the passive/inclusive sensor type, is a sensor that represents a tool operational parameter that does not correlate strongly with the active

type sensors, but which is expected from operator experience to provide important tool fault information. An example of a passive/inclusive sensor type is susceptor temperature sensor 120 in Fig. 1B. The susceptor temperature of plasma etching tool 102 does not correlate strongly with the active (pressure) sensors 106a-d, but it is known from user experience that susceptor temperature is a key fault indicia for the particular etch process being monitored. Thus, embodiments of the invention include passive/inclusive sensor 120 in calculation of a fault detection index, even where the active type sensors used to predict the output vector comprise a set of correlating tool pressures. Passive/inclusive type sensors are not utilized in the nearest neighbor selection process, but are utilized in generating the fault detection index.

Finally, a fourth class of sensor is the synthetic sensor type, which may be employed to expand the predictive capability of the model. Specifically, synthetic type sensors represent physical quantities that cannot be measured during real time operation of the tool, but which can be measured and assigned to a particular vector upon completion of the semiconductor process. In the specific example of Fig. 1B, a synthetic sensor type 122 represents a critical dimension (CD) of a semiconductor feature resulting from plasma etching. The CD cannot be measured during etching, but can be measured after etching and then be included as a component of a library vector. Subsequent selection of nearest neighbor vectors would result in prediction of a critical dimension.

Synthetic sensor types are merely predicted by the model, and are not utilized in the selection process of the nearest neighbor vectors or in generating the fault detection index. Input of the synthetic type sensor 122 is not required by the model and input vector 104 includes a null value for synthetic type sensor 122.

However, as discussed below, the output vector produced by the model includes a predicted value for the synthetic type sensor 122.

For reference, a general summary of the role of each sensor type is listed below in TABLE 1.

TABLE 1

SENSOR TYPE	EXAMPLE	INPUT REQUIRED?	VALUE PREDICTED BY MODEL?	CORRELATION WITH OTHER ACTIVE SENSORS?	USED TO SELECT VECTOR SUBSET?	USED TO CALCULATE FAULT DETECTION INDEX?
Active	chamber pressure	Yes	Yes	Yes	Yes	Yes
Passive/ Inclusive	susceptor temperature	Yes	Yes	No	No	Yes
Synthetic	out 1	No	Yes	Not Applic.	No	No
Cluster	stage	Yes	No	Not Applic.	Yes	No

Returning to Fig. 1A, once the input vector has been sampled from the semiconductor fabrication tool, the next step is to compare the input vector to the reference library compiled during prior normal operation of the tool. Referring back to the nearest neighbor algorithm of step 10, the example shown in Fig. 1B employs two steps to gauge similarity between input vector 104 and vectors 170-179 of reference data library 112. In a first test, input vector 104 is compared with reference data library 112 and similarity factor 124 is generated for each of vectors 170-179. Similarity factor 124 reflects similarity to active type sensors 106a-d of input vector 104. One approach to generating similarity factor 124 may be through the operation of the proprietary UPM software program previously described. Vectors having a similarity factor 124 exceeding a cut-off value (0.97 in the example of Fig. 1B) pass the first test. The values of passive/inclusive type sensor 120 and synthetic type sensor 122 are not included in calculating similarity factor 124. As shown in Fig. 1B, vectors 170, 172, 173, 177, and 178 pass the first test.

In the second test, cluster type sensor 118 of input vector 104 is compared with cluster type sensors of the vectors of reference data library 112. In the example shown in Fig. 1B, this comparison test requires identity between the cluster sensors (i.e., only reference data library vectors at stage 1 pass the second test). Alternatively, this comparison test may require less than an exact match between the cluster sensor types (i.e., where the cluster sensor is quantified in units of seconds rather than “stages”, library vectors measured within a specific range of seconds of the input vector may pass the second test). As shown in Fig. 1B, library vectors 170, 172, 177, and 178 also pass the second test. Vector 173 fails the second test because of non-identity between its cluster type sensor component and that of input vector 104.

Next in step 12, vector subset 108 is compiled from library vectors 170, 172, 177, and 178 satisfying both the first and the second tests. The vectors of subset 108 include predicted values for the active, cluster, passive/inclusive, and synthetic sensor types.

5 In step 14, vectors 170, 172, 177, and 178 of vector subset 108 are combined to produce an output prediction vector 116. In the specific example shown in Fig. 1B, output prediction vector 116 is generated by assigning a first set of weights 126 to vectors 170, 172, 177, and 178, and then combining the weighted vectors. Alternatively, this vector combination step could utilize no weighting at all and assign
10 equal weight to each vector of the subset. As yet another alternative, the combination could utilize a weighing system that considers similarity factor 124 previously generated for each vector.

In step 16, fault detection index 114 is generated from output prediction vector 116. Sensor ranking is an additional technique that may be employed to
15 improve the accuracy of fault detection. Active and passive/inclusive type sensors of vector 116 may be ranked in terms of their relative importance in indicating a tool fault utilizing second set of weights 128. The weighted sensor values can then be combined to produce fault detection index 114. The values of synthetic type sensor 122 and cluster type sensor 118 are not included in this calculation.

20 Experimental results of fault detection in accordance with the present invention are now described below in connection with Figures 3A-9C.

Experimental Results

I. Sensor Grouping

25 Plasma etching of oxide layers is frequently performed during the formation of vias in integrated circuits. As a result of oxide etching, polymer materials may accumulate that interfere with correct positioning of the wafer. This can affect product yields. Ordinarily the polymer residues are removed by periodic cleaning steps.

30 To evaluate a fault detection method in accordance with the present invention, a series of over 1400 consecutive oxide plasma etching runs utilizing an Applied Materials Centura® plasma etching device were performed, without any intervening cleaning steps. Tool sensor information was collected and modeled

utilizing Modelware/RT software manufactured by Triant Technologies, Inc. of Nanaimo, British Columbia.

Residual values represent the difference between an actual measured value from the tool and a value predicted by the model. Figs. 2A-2C plot the residual value of foreline pressure, at the beginning, middle, and end of the series of processing runs. Fig. 2A plots values for residual foreline pressure for a beginning portion the 1400 consecutive test runs. Fig. 2A shows that values for residual foreline pressure at first remained comfortably within expected tolerance region X.

Fig. 2B plots values for residual foreline pressure for an intermediate portion of the test runs. Fig. 2B shows a drift in the residual value of foreline pressure to the lowermost portion of tolerance region X.

Fig. 2C plots values for foreline pressure for a later portion of the test runs. Fig. 2C shows that the drift in the residual value of foreline pressure indicated in Fig. 2B has continued, such that the foreline pressure is now out of the tolerance region X. With conventional fault detection methods, this trend would likely alarm the tool and halt wafer production. However, correlation of the foreline pressure data with other tool information, and hence the actual existence of a fault, would remain undetermined.

Therefore, the state of the plasma etching tool over the same series of 1400 consecutive processing runs was examined utilizing four specialized fault detection indices, each including different active sensor groupings. The active sensors for each fault detection index are listed below in TABLE 2.

TABLE 2

ACTIVE SENSOR NO.	FIRST FAULT DETECTION INDEX	SECOND FAULT DETECTION INDEX	THIRD FAULT DETECTION INDEX	FOURTH FAULT DETECTION INDEX
1	chamber pressure	chamber wall temperature	DC bias	chuck current
2	throttle valve position	chuck temperature	forward power	chuck voltage
3	foreline pressure	heat exchanger temperature	reflected power	inner helium flow
4	gas 1 inlet pressure	cathode temperature	load blade position	outer helium flow
5	gas 2 inlet pressure	none	tune blade position	inner helium pressure
6	none	none	none	outer helium pressure

TABLE 2 illustrates the reduction in data offered by sensor grouping. Specifically, information of a total of 20 sensors is condensed into just four fault detection indices.

The enhanced precision of fault detection offered by the indices of TABLE 2 is discussed below in conjunction with Figs. 3-7D. Fig. 3 plots the second fault detection index over the entire processing run of >1400 wafers. This second fault detection index, which focuses upon temperature, does not reveal a fault in the plasma etching tool.

Fig. 4 plots the third fault detection index over the processing run. Apart from a single fault at around wafer 200, this third index focusing upon power also does not reveal a tool fault. The spike at around wafer 200 was associated with etching of a bare silicon wafer lacking an oxide layer that was inadvertently placed into the etching tool.

Fig. 5 plots the fourth fault detection index over the processing run. This third fault detection index, which focuses upon wafer chucking, reveals an initial fault at around wafer 600, followed with increasingly frequent faults. The fourth fault detection index indicates a likely problem with chucking of the wafer about halfway through the 1400+ test runs. This was likely due to the buildup of residues due to an absence of periodic cleaning steps.

Fig. 6 plots the first fault detection index over the processing run. This first fault detection index, which focuses upon pressure, reveals a fault at about wafer 200, corresponding to processing of the bare silicon wafer. Moreover, Fig. 6 also

reveals an increase in the incidence of tool fault after about wafer number 600. This trend in the first fault detection index further indicates a tool fault.

In order to more specifically examine the causes of the tool fault indicated by Figures 5 and 6, Figs. 7A-7D plot values for several of the active sensors of the first fault detection index during portion “Z” occurring late in the series of processing runs shown in Figs. 3-6.

Fig. 7A plots the gas 1 inlet flow. Fig. 7A indicates that the gas 1 flow inlet pressure remained within tolerance band X. The fault indicated by the fourth fault detection index was thus not attributable to gas 1 inlet flow pressure.

Fig. 7B plots foreline pressure sensor for same portion Z of Fig. 7A. Fig. 7B indicates that foreline pressure was out of tolerance band X.

Fig. 7C plots the throttle valve sensor for the same portion Z of Fig. 7A. Fig. 7D plots the chamber pressure sensor for portion Z. Figs. 7C and 7D reveal that the throttle valve and chamber pressure lie substantially out of acceptable tolerance band X.

The value of the sensor readings of Figs. 7A-7D, and their correlation to one another, confirm the existence of a tool fault as initially indicated by the decline in foreline pressure shown in Figs. 2A-2C. When combined, the throttle value, foreline pressure, and chamber pressure active sensor values account for the decline in the fourth fault detection index, and provide a more accurate picture of the status of the plasma etching tool than any single sensor considered independently.

B. Cluster Sensor

While the above experimental results illustrate the impact of sensor grouping in revealing the existence of a tool fault, utilization of the cluster sensor also enhances the accuracy of fault detection.

Fig. 8A plots a fault detection index versus time for a process run of a plasma etching tool experiencing a tool fault. The method of Fig. 8A considers the value of the cluster sensor in the selection process of the nearest neighbor vectors to compile the vector subset. Fig. 8A represents a highly accurate picture of the status of the tool, with the fault detection index progressively worsening from time T_1 until the tool is ultimately halted and alarmed at time T_2 .

By contrast, Fig. 8B plots the same process run where the value of the cluster sensor is not included in the selection process of the nearest neighbor vectors to

compile the vector subset. Fig. 8B represents a less accurate picture of the status of the tool, with an abrupt drop in the fault detection index occurring at time T_3 immediately prior to alarming and halting of the tool at time T_4 . The advance warning of a fault provided by the method of Fig. 8A would afford the tool operator significant lead time to recognize and correct a fault. Early fault recognition would thus reduce the number of wafers ultimately falling outside of acceptable tolerances, raising tool yields.

C. Passive/Inclusive Sensor

Utilization of the passive/inclusive sensor type also provides benefits in fault detection. For example, an operational parameter such as susceptor temperature may provide important fault detection information. However, susceptor temperature does not correlate strongly with the related active pressure sensors of the first fault detection index of TABLE 2.

If the susceptor temperature is defined as an active sensor, it is included in the nearest neighbor selection process. However, this is undesirable where the tool performance is to be modeled based upon other strongly correlating sensors. The role of the passive/inclusive sensor type is best understood in conjunction with FIGS. 9A-9C below.

Fig. 9A plots measured susceptor temperature and the predicted susceptor temperature range over time, for a properly functioning etch tool. Both measured and predicted susceptor temperature are cyclical between times T_1 and T_2 .

Fig. 9B plots measured susceptor temperature and the predicted susceptor temperature range over time, in a predictive model in which the susceptor temperature is an active sensor type. Fig. 9B indicates that at time T_1 the tool experiences a fault and the measured susceptor temperature departs from its expected cyclical behavior, remaining constant through T_2 . Susceptor temperature does not correlate strongly with the group of related active pressure sensors. However, because susceptor temperature is an active sensor type and is considered in selection of the nearest neighbor vectors, the vector subset predicted by the model reflects the flat shape that conforms to the change in actual temperature. This change in predicted temperature masks the tool fault indicated by the constant flat profile of measured temperature between times T_1 and T_2 .

By contrast, Fig. 9C plots the measured susceptor temperature and a predicted susceptor temperature range over time, in a predictive model in which

susceptor temperature is a passive/inclusive sensor type. Like the tool of Fig. 9B, the tool of Fig. 9C experiences a fault at time T_1 . However, because the measured susceptor temperature is not included in selecting the nearest neighbor vectors of the subset, the predicted susceptor temperature range does not remain flat at time T_1 to match the measured value. Rather, in Fig. 9C the flat profile in actual susceptor temperature beginning at time T_1 passes outside of the predicted range and is thus recognizable as a tool fault.

Apparatus for Fault Detection

Fig. 10 shows a simplified view of an apparatus configured to practice an embodiment of a method in accordance with the present invention. Apparatus 1000 includes semiconductor fabrication tool 1002 including wafer processing chamber 1004 having wafer 1006 positioned therein. Apparatus 1000 also includes first sensor 1008 and second sensor 1010 operatively coupled to tool 1002 to detect operational parameters of tool 1002.

Controller 1012 is in communication with tool 1002, and with first and second sensors 1008 and 1010. Memory 1014 is coupled to controller 1012, and memory 1014 stores a computer program in computer readable format including computer instructions to control said apparatus to sense a group of correlating operational parameters from the semiconductor processing tool operating under a recipe. The computer instructions also control said apparatus to compare the group of correlating operational parameters to corresponding operational parameters recorded during prior runs of the tool utilizing the recipe, and to generate a fault detection index from comparing the sensed group of operational parameters to the corresponding operational parameters recorded during prior runs.

While the present invention has been described in Fig. 1B in conjunction with detecting a fault in a plasma etching tool, the semiconductor fabrication tool of Fig. 10 is not limited to this specific embodiment. In accordance with one alternative embodiment of the present invention, a fault in a chemical-mechanical polishing (CMP) apparatus could be detected. In accordance with other alternative embodiments of the present invention, faults in other semiconductor fabrication tools such as chemical vapor deposition tools and lithography apparatuses could be detected.

In addition, the above invention has been described in conjunction with a fault detection method utilizing selection of nearest neighbor vectors from a reference

data library, this is not required by the present invention. The technique of grouping together sensors that correlate with one another to create fault detection indices could be utilized in other modeling approaches, and the method would still remain within the scope of the present invention.

- 5 Given the above detailed description of the present invention and the variety of embodiments described therein, these equivalents and alternatives along with the understood obvious changes and modifications are intended to be included within the scope of the present invention.

10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000